NSN 5925-00-045-8091

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-045-8091 **Overall Length:** 1.750 inches **Overall Height:** 2.570 inches Overall Width: 0.630 inches **Case Material:** Metal **Pole Quantity: Mounting Facility Type And Quantity:** Thd bushing Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 4.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 500.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type: Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Thread Size:** 0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.150 at 200 pct single location and 0.800 at 200 pct single location and 0.050 at 300 pct single location and 0.370 at 300 pct single location and 0.010 at 400 pct single location and 0.190 at 400 pct single location

Inclosure Protection Type For Which Designed:

Hermetically sealed

NSN 5925-00-045-8091

Circuit Breaker - Page 2 of 2



Frequency in Hertz:
400.0 single location
Thread Series Designator:
Unef
Terminal Type And Quantity:
2 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0