NSN 5925-00-052-4845



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-052-4845 **Body Style:** Rectangular dimensional envelope **Overall Length:** 3.500 inches **Overall Height:** 1.500 inches **Overall Width:** 2.500 inches **Case Material:** Plastic **Pole Quantity: Mounting Facility Type And Quantity:** 6 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 7.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 1.000 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

At pole two

Actuator Position Designation:

NSN 5925-00-052-4845 Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.250 at 200 pct all locations and 0.900 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0