

View Online at <https://aerobasegroup.com/nsn/5925-00-054-8655>

Overall Length:

1.960 inches

Body Width:

0.730 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.000 inches

Unthreaded Mounting Hole Diameter:

0.157 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.370 inches

Mounting Surface To Terminal End Distance:

2.170 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location and 10.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100.0 ac single location and 100.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

100.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

40.000 at 200 pct single location and 18.000 at 300 pct single location

Inclsoure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

20.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0