## NSN 5925-00-054-8656



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-054-8656 **Body Style:** Single pole type **Overall Length:** 1.970 inches **Overall Width:** 0.730 inches **Case Material:** Plastic **Unthreaded Mounting Hole Diameter:** 0.180 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.570 inches **Boss Height:** 0.280 inches **Mounting Surface To Terminal End Distance:** 1.970 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 4.0 amperes ac single location and 4.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location and 24.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 40.0 ac single location and 40.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 push button **Actuator Function:** 

At pole one

**Actuator Position Designation:** 

Trip-reset

# NSN 5925-00-054-8656

Circuit Breaker - Page 2 of 2



### **Internal Trip Release Configuration:**

Series trip single location

### **Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct single location and 40.000 at 200 pct single location and 3.000 at 300 pct single location and 18.000 at 300 pct single location and 2.000 at 400 pct single location and 9.000 at 400 pct single location

### **Trip Release Ambient Tempurature Rating:**

20.0 degrees celsius single location

### **Terminal Type And Quantity:**

2 quick disconnect, male

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0