NSN 5925-00-055-9374

Circuit Breaker - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5925-00-055-9374

Multipole-multiple actuator type **Body Length:** 2.500 inches **Body Width:** 1.520 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.190 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.000 inches **Pole Quantity:** 2 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 2.5 amperes ac all locations and 2.5 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations and 50.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac all locations and 3000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic-hydraulic all locations

NSN 5925-00-055-9374 Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.380 at 800 pct pascal all locations and 1.200 18 stage pascal all locations
Inclosure Protection Type For Which Designed:
Dustproof and fungus resistant
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
4.250 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0