NSN 5925-00-055-9374

Circuit Breaker - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5925-00-055-9374

Multipole-multiple actuator type **Body Length:** 2.500 inches **Body Width:** 1.520 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.190 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.000 inches **Pole Quantity:** 2 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 2.5 amperes ac all locations and 2.5 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations and 50.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac all locations and 3000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic-hydraulic all locations

NSN 5925-00-055-9374 Circuit Breaker - Page 2 of 2



| Trip Release Characteristic: |
|---|
| Time delay all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 all locations |
| Reset Method: |
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 2 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At each pole |
| External Actuator Linkage Arrangement: |
| One and two linked |
| Internal Trip Release Configuration: |
| Series trip all locations |
| Thread Size: |
| 0.138 inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 0.380 at 800 pct pascal all locations and 1.200 18 stage pascal all locations |
| Inclosure Protection Type For Which Designed: |
| Dustproof and fungus resistant |
| Frequency In Hertz: |
| 60.0 all locations |
| Unpackaged Unit Weight: |
| 4.250 ounces |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 4 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |