

View Online at <https://aerobasegroup.com/nsn/5925-00-056-8931>

**Case Material:**

Plastic

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 terminal

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac single location and 15.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location and 125.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac single location and 5000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal-magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Nontrip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

60.000 at 150 pct single location and 100.000 at 150 pct single location

**Inclosure Protection Type For Which Designed:**

General purpose

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0