

View Online at <https://aerobasegroup.com/nsn/5925-00-058-3004>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

1.500 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.938 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.060 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.150 inches

**Mounting Surface To Terminal End Distance:**

2.611 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac second location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac second location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac first location

**Circuit Protection Type:**

Overcurrent first location

**Trip Release Method:**

Magnetic-hydraulic first location

**Trip Release Characteristic:**

Instantaneous first location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 first location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One and two linked

**Internal Trip Release Configuration:**

Series trip first location

**Thread Size:**

0.138 inches

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Special Features:**

Second pole switch only

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0