

View Online at <https://aerobasegroup.com/nsn/5925-00-058-3004>

Body Style:

Multipole-multiple actuator type

Body Length:

2.500 inches

Body Width:

1.500 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.938 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.150 inches

Mounting Surface To Terminal End Distance:

2.611 inches

Pole Quantity:

2

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac second location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac first location

Circuit Protection Type:

Overcurrent first location

Trip Release Method:

Magnetic-hydraulic first location

Trip Release Characteristic:

Instantaneous first location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 first location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip first location

Thread Size:

0.138 inches

Inclosure Protection Type For Which Designed:

Fungus resistant

Special Features:

Second pole switch only

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0