NSN 5925-00-058-7941

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-058-7941 **Body Style:** Rectangular dimensional envelope **Overall Length:** 26.906 inches **Overall Height:** 6.875 inches **Overall Width:** 9.000 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.250 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 150.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 25000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

Manual Actuator Type And Quantity:

1 toggle

NSN 5925-00-058-7941 Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+750.0 to 1600.0 ac all locations
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
105.000 at 200 pct all locations and 40.000 at 300 pct all locations
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0