NSN 5925-00-060-6732

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-060-6732

## Body Style:

Multipole-single actuator type

## Body Length:

6.250 inches

# Body Width:

2.234 inches

## **Body Height:**

2.468 inches

## Case Material:

Plastic

# Center To Center Distance Between Terminals Parallel To Width:

0.734 inches

## **Boss Height:**

0.156 inches

## Pole Quantity:

3

#### Mounting Facility Type And Quantity:

6 terminal

#### Storage Type:

General purpose warehouse

#### Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### Trip Release Method:

Thermal-magnetic all locations

#### Trip Release Characteristic:

Instantaneous all locations and time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

#### Manual Actuator Type And Quantity:

1 toggle

#### **Actuator Function:**

Trip-reset

# NSN 5925-00-060-6732

Circuit Breaker - Page 2 of 2



**Actuator Position Designation:** 

At pole two

Trip Delay Time In Seconds Per Rated Continuous Current:

25.000 at 200 pct all locations and 40.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius all locations

**Frequency In Hertz:** 

60.0 all locations

Terminal Type And Quantity:

3 clip and 3 screw

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0