NSN 5925-00-062-6936

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-062-6936

Body Style:
Multipole-single actuator type
Body Length:
9.500 inches
Body Width:
4.125 inches
Body Height:
4.062 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
8.000 inches
Center To Center Distance Between Terminals Parallel To Width:
1.375 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
7.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Boss Height:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
150.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
15000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

NSN 5925-00-062-6936 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A030a0