

View Online at <https://aerobasegroup.com/nsn/5925-00-063-8996>

**Case Material:**

Plastic

**Switch Contact Arrangement:**

Single pole, double throw

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded stud

**Thread Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac and 50.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac and 10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous and time delay all locations

**Reset Method:**

Manual

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Reset

**Actuator Position Designation:**

At each pole

**Auxiliary Switch Function And Quantity:**

1 alarm

**Thread Size:**

0.190 inches

**Switch Location And Position Designation:**

Internal at pole one

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Switch Terminal Type:**

Wire lead

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0