

View Online at <https://aerobasegroup.com/nsn/5925-00-063-8996>

Case Material:

Plastic

Switch Contact Arrangement:

Single pole, double throw

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded stud

Thread Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac and 50.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous and time delay all locations

Reset Method:

Manual

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Actuator Position Designation:

At each pole

Auxiliary Switch Function And Quantity:

1 alarm

Thread Size:

0.190 inches

Switch Location And Position Designation:

Internal at pole one

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Switch Terminal Type:

Wire lead

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0