# NSN 5925-00-064-9726

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-064-9726

#### **Body Style:**

Multipole-single actuator type

#### **Body Length:**

6.062 inches

### Body Width:

4.125 inches

#### **Body Height:**

3.406 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

#### 5.219 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.375 inches

**Unthreaded Mounting Hole Diameter:** 

#### 0.225 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

#### Boss Height:

0.219 inches

#### Pole Quantity:

3

# Mounting Facility Type And Quantity:

4 unthreaded hole

# Storage Type:

General purpose warehouse

# Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

# Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations

# **Circuit Protection Type:**

Overcurrent all locations

# Trip Release Method:

Thermal-magnetic all locations

# Trip Release Characteristic:

Time delay all locations

# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

# **NSN 5925-00-064-9726** Circuit Breaker - Page 2 of 2



М	anual
М	ain Contact Tripping Mechanism Type:
т	rip free
м	anual Actuator Type And Quantity:
1	toggle
A	ctuator Function:
Tr	rip-reset
A	ctuator Position Designation:
A	t pole two
Tı	rip Delay Time In Seconds Per Rated Continuous Current:
15	5.000 at 200 pct all locations and 39.000 at 200 pct all locations
In	closure Protection Type For Which Designed:
F١	ungus resistant
Tı	rip Release Ambient Tempurature Rating:
4(	0.0 degrees celsius all locations
Fı	requency In Hertz:
60	0.0 all locations
Te	erminal Type And Quantity:
6	compression
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
N	0
Fi	iig:
A	030a0