

View Online at <https://aerobasegroup.com/nsn/5925-00-066-6890>

Overall Length:

9.380 inches

Overall Height:

2.750 inches

Overall Width:

4.690 inches

Case Material:

Plastic

Pole Quantity:

2

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations and 30.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations and 5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

117.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip w/separate reset

Thread Size:

0.281 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

75.000 at 150 pct all locations and 360.000 at 150 pct all locations and 20.000 at 200 pct all locations and 63.000 at 200 pct all locations and 8.000 at 300 pct all locations and 15.000 at 300 pct all locations and 4.000 at 400 pct all locations and 8.000 at 400 pct all locations and 2.500 at 500 pct all locations and 4.500 at 500 pct all locations and 0.030 at 1100 pct all locations and 1.000 at 1100 pct all locations and 0.010 at 2000 pct all locations and 0.020 at 2000 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Special Features:

Mtg holes On 7.250 in. By 1.375 in. Mtg centers

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0