

View Online at <https://aerobasegroup.com/nsn/5925-00-066-6896>

**Overall Length:**

2.500 inches

**Overall Height:**

3.170 inches

**Overall Width:**

0.750 inches

**Case Material:**

Plastic

**Pole Quantity:**

1

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

2 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

6.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Instantaneous single location and time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Thread Size:**

0.138 inches

**Trip Release Duty Cycle:**

Continuous single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

7.000 at 150 pct single location and 25.000 at 150 pct single location and 3.000 at 200 pct single location and 9.000 at 200 pct single location and 1.200 at 300 pct single location and 3.500 at 300 pct single location and 0.300 at 500 pct single location and 1.000 at 500 pct single location and 0.010 at 1000 pct single location and 0.040 at 1000 pct single location

**Inclosure Protection Type For Which Designed:**

Dustproof

**Special Features:**

Mtg holes on 2 1/16 in. Centers

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0