

View Online at <https://aerobasegroup.com/nsn/5925-00-066-6896>

Overall Length:

2.500 inches

Overall Height:

3.170 inches

Overall Width:

0.750 inches

Case Material:

Plastic

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

6.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Thread Size:

0.138 inches

Trip Release Duty Cycle:

Continuous single location

Trip Delay Time In Seconds Per Rated Continuous Current:

7.000 at 150 pct single location and 25.000 at 150 pct single location and 3.000 at 200 pct single location and 9.000 at 200 pct single location and 1.200 at 300 pct single location and 3.500 at 300 pct single location and 0.300 at 500 pct single location and 1.000 at 500 pct single location and 0.010 at 1000 pct single location and 0.040 at 1000 pct single location

Inclosure Protection Type For Which Designed:

Dustproof

Special Features:

Mtg holes on 2 1/16 in. Centers

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0