NSN 5925-00-067-3814

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-067-3814 **Body Length:** 6.000 inches **Body Width:** 1.484 inches **Body Height:** 2.312 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Boss Height:** 0.156 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations and 15.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 7500.0 ac all locations and 7500.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Position Designation:**

Internal Trip Release Configuration: Series trip all locations

Between pole one and two

NSN 5925-00-067-3814

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

7.000 at 300 pct all locations and 10.000 at 300 pct all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A030a0