NSN 5925-00-067-8322



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-067-8322 **Body Length:** 5.250 inches **Body Width:** 3.000 inches **Case Material: Plastic** Center To Center Distance Between Terminals Parallel To Length: 3.062 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.359 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.984 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.219 inches **Mounting Surface To Terminal End Distance: 3.313** inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 4 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 70.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:**

Magnetic all locations **Trip Release Characteristic:** Time delay all locations

NSN 5925-00-067-8322

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Ultimate Trip Time Per Pole In Seconds:
150.000 all locations and 800.000 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.164 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
36.000 at 200 pct all locations and 115.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Moisture resistant and fungus resistant
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
29.000 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0