NSN 5925-00-069-7148



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-069-7148 **Body Style:** Rectangular dimensional envelope **Overall Length:** 3.469 inches **Overall Height:** 1.000 inches **Overall Width:** 1.125 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 20 **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location and 5.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location and 50.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 200.0 ac single location and 200.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 push button

Trip-reset

Actuator Function:

NSN 5925-00-069-7148Circuit Breaker - Page 2 of 2



| Actuator Position Designation: |
|---|
| At pole one |
| Internal Trip Release Configuration: |
| Series trip single location |
| Thread Size: |
| 0.750 inches |
| Inclosure Protection Type For Which Designed: |
| Fungus resistant and moisture resistant |
| Trip Release Ambient Tempurature Rating: |
| 25.0 degrees celsius single location |
| Frequency In Hertz: |
| 60.0 single location |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 2 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |