

View Online at <https://aerobasegroup.com/nsn/5925-00-070-4387>

Body Style:

Multipole-single actuator type

Body Length:

4.125 inches

Body Width:

3.344 inches

Body Height:

3.375 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

2.625 inches

Center To Center Distance Between Terminals Parallel To Width:

1.125 inches

Unthreaded Mounting Hole Diameter:

0.228 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.938 inches

Boss Height:

0.125 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 clip

Specification Or Standard:

Alb5 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0