# NSN 5925-00-072-9933

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-072-9933

# Body Style:

- Single pole type
- **Bushing Length:**
- 0.250 inches

#### **Body Length:**

2.188 inches

#### **Body Width:**

0.750 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

Between 1.158 inches and 1.218 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.807 inches and 1.817 inches

#### **Fragility Factor:**

Moderately rugged

# Mounting Surface To Terminal End Distance:

2.000 inches

# **Pole Quantity:**

1

#### Mounting Facility Type And Quantity:

1 threaded hole

#### Storage Type:

General purpose warehouse

#### Thready Qty Per Inch (tpi):

32

#### Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location and 15.0 amperes dc single location

#### **Operating Voltage Type And Rating Per Pole In Volts:**

200.0 ac single location and 28.0 dc single location

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location and 5000.0 dc single location

#### **Circuit Protection Type:**

Overcurrent single location

#### Trip Release Method:

Thermal single location

#### **Trip Release Characteristic:**

Time delay single location

# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

#### **Reset Method:**

Manual

# NSN 5925-00-072-9933

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 push-pull **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 15.000 at 200 pct single location and 55.000 at 200 pct single location **Inclosure Protection Type For Which Designed:** Fungus resistant and moisture resistant **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius single location Frequency In Hertz: 400.0 single location **Unpackaged Unit Weight:** 0.158 pounds **Thread Series Designator:** Uns **Terminal Type And Quantity:** 2 tab w/screw Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0