

View Online at <https://aerobasegroup.com/nsn/5925-00-078-1705>

Body Style:

Multipole-multiple actuator type

Body Length:

5.250 inches

Body Width:

4.500 inches

Body Height:

2.689 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

4.359 inches

Center To Center Distance Between Terminals Parallel To Width:

0.984 inches

Unthreaded Mounting Hole Diameter:

0.190 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.984 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.218 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

12 threaded hole and 12 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

200.0 milliamperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

440.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.164 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 200 pct all locations and 20.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof and fungus proof

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0