NSN 5925-00-080-7124



Circuit Breaker Tripper - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5925-00-080-7124 **Unthreaded Mounting Hole Diameter:** 0.188 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 3 unthreaded hole Storage Type: General purpose warehouse **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 600.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 160.0 all locations Adjustable Trip Setting Current Range Per Pole In Amps: +80.0 to 160.0 ac all locations **Internal Trip Release Configuration:** Series trip all locations **Trip Delay Time In Seconds Per Rated Continuous Current:** 130.000 at 300 pct all locations Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 6 bus bar Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A030a0