

View Online at <https://aerobasegroup.com/nsn/5925-00-080-9284>

**Body Style:**

Single pole type

**Overall Length:**

1.969 inches

**Overall Width:**

0.993 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.340 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.000 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Boss Height:**

0.120 inches

**Mounting Surface To Terminal End Distance:**

1.910 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

4.0 amperes ac single location and 4.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

230.0 ac single location and 120.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

200.0 ac single location and 200.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip w/separate reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip w/dual rating single location

**Thread Size:**

0.138 inches

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

23.000 at 200 pct single location and 4.400 at 300 pct single location

**Trip Release Ambient Temperature Rating:**

24.0 degrees celsius single location

**Switch Terminal Type:**

Screw

**Switch Current Rating And Type In Amps:**

3.0 ac and 3.0 dc

**Switch Voltage Rating And Type In Volts:**

115.0 ac and 50.0 dc

**Frequency In Hertz:**

400.0 single location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 eyelet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0