# NSN 5925-00-081-3823

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-081-3823

#### **Body Style:**

Multipole-single actuator type

#### **Bushing Length:**

Between 0.280 inches and 0.380 inches

#### **Body Length:**

1.562 inches

#### **Body Width:**

1.937 inches

#### **Case Material:**

Metal

#### Center To Center Distance Between Terminals Parallel To Length:

0.906 inches

#### Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

### Fragility Factor:

Moderately rugged

#### Mounting Surface To Terminal End Distance:

1.828 inches

## **Pole Quantity:**

3

#### Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

#### Storage Type:

General purpose warehouse

#### **Special Handling Feature:**

Magnetic

#### Thready Qty Per Inch (tpi):

32

#### Maximum Continuous Load Current Rating Per Pole:

750.0 milliamperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

# NSN 5925-00-081-3823

Circuit Breaker - Page 2 of 2



Reset	Method:
Manua	al
Main (	Contact Tripping Mechanism Type:
Trip fr	ee
Manua	al Actuator Type And Quantity:
1 togg	le
Actua	tor Function:
Trip-re	eset
Actua	tor Position Designation:
At pole	e two
Intern	al Trip Release Configuration:
Series	trip all locations
Threa	d Size:
0.375	inches
Inclos	sure Protection Type For Which Designed:
Vibrati	on resistant and shock resistant and moisture resistant and salt spray proof and hermetically sealed
Frequ	ency In Hertz:
400.0	all locations
Unpad	ckaged Unit Weight:
4.500	ounces
Test D	Data Document:
13499	-260-4044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
exclu	des any specification, standard or other document that may be referenced in a basic governing drawing)
Threa	d Series Designator:
Unef	
Termi	nal Type And Quantity:
6 wire	hook
Shelf	Life:
N/a	
Unit C	Of Measure:
Demil	itarization:
No	
Fiig:	
A030a	0