NSN 5925-00-083-6042

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-083-6042 **Body Style:** Multipole-single actuator type **Body Length:** 6.000 inches **Body Width:** 4.125 inches **Body Height:** 3.375 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.375 inches **Unthreaded Mounting Hole Diameter:** 0.188 inches **Boss Height:** 0.125 inches **Pole Quantity: Arc Quenching Method:** Deion **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 480.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual

Main Contact Tripping Mechanism Type: Trip free

NSN 5925-00-083-6042 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
120.000 at 200 pct all locations
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
4030a0