

View Online at <https://aerobasegroup.com/nsn/5925-00-086-8450>

Body Style:

Multipole-multiple actuator type

Body Length:

2.875 inches

Body Width:

3.000 inches

Body Height:

2.375 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

1.000 inches

Boss Height:

0.156 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 terminal

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Trip Delay Time In Seconds Per Rated Continuous Current:

7.000 at 150 pct all locations and 3.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

15.000 ounces

Terminal Type And Quantity:

3 clip and 3 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0