NSN 5925-00-087-7506

Circuit Breaker - Page 1 of 2

Thermal-magnetic all locations



View Online at https://aerobasegroup.com/nsn/5925-00-087-7506

| Body Style: |
|--|
| Multipole-single actuator type |
| Bushing Length: |
| 0.318 inches |
| Body Length: |
| 2.200 inches |
| Body Width: |
| 2.270 inches |
| Body Height: |
| 2.370 inches |
| Case Material: |
| Metal |
| Center To Center Distance Between Terminals Parallel To Length: |
| 1.190 inches |
| Center To Center Distance Between Terminals Parallel To Width: |
| 1.500 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Between 1.800 inches and 1.820 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.750 inches |
| Fragility Factor: |
| Moderately rugged |
| Pole Quantity: |
| 3 |
| Mounting Facility Type And Quantity: |
| 4 threaded hole |
| Storage Type: |
| General purpose warehouse |
| Special Handling Feature: |
| Magnetic |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 5.0 amperes ac all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 120.0 ac all locations |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 5000.0 ac all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |

NSN 5925-00-087-7506 Circuit Breaker - Page 2 of 2



| Trip Release Characteristic: |
|--|
| Time delay all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 140.0 all locations |
| Reset Method: |
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 push-pull |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole two |
| Thread Size: |
| 0.138 inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 10.000 at 200 pct all locations and 70.000 at 200 pct all locations |
| Inclosure Protection Type For Which Designed: |
| Corrosion resistant and humidity resistant and shock resistant and hermetically sealed |
| Trip Release Ambient Tempurature Rating: |
| 77.0 degrees fahrenheit all locations |
| Frequency In Hertz: |
| 400.0 all locations |
| Unpackaged Unit Weight: |
| 0.650 pounds |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 6 tab w/screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A030a0 |
| |