## NSN 5925-00-089-2092

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-089-2092

Body Style:					
Rectangular dimensional envelope					
Overall Length:					
8.500 inches					
Overall Height:					
3.875 inches					
Overall Width:					
4.500 inches					
Fragility Factor:					
Moderately rugged					
Pole Quantity:					
3					
Mounting Facility Type And Quantity:					
6 terminal					
Storage Type:					
General purpose warehouse					
Special Handling Feature:					
Magnetic					
Features Provided:					
Adjustable trip release					
Maximum Continuous Load Current Rating Per Pole:					
350.0 amperes ac all locations and 350.0 amperes dc all locations					
Operating Voltage Type And Rating Per Pole In Volts:					
500.0 ac all locations and 250.0 dc all locations					
Circuit Protection Type:					
Overcurrent all locations					
Trip Release Method:					
Thermal-magnetic all locations					
Trip Release Characteristic:					
Time delay all locations					
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:					
140.0 all locations					
Manual Actuator Type And Quantity:					
1 toggle					
Actuator Function:					
Trip-reset					
Actuator Position Designation:					
At pole two					
Adjustable Trip Setting Current Range Per Pole In Amps:					
+2020 0 to 3420 0 ac, and +2020 0/+3420 0 dc all locations					

Trip Delay Time In Seconds Per Rated Continuous Current:

300.000 at 200 pct all locations and 900.000 at 200 pct all locations

## NSN 5925-00-089-2092

Circuit Breaker Tripper - Page 2 of 2



Trin	Release	<b>Ambient</b>	<b>Tempurature</b>	Rating:
III	Neicase		I CIIIDUI ALUI C	ivatilia.

40.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

**Terminal Type And Quantity:** 

6 quick disconnect, male

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A030a0