

View Online at <https://aerobasegroup.com/nsn/5925-00-092-0578>

Body Style:

Single pole type

Overall Length:

2.000 inches

Body Width:

0.780 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.682 inches

Unthreaded Mounting Hole Diameter:

Between 0.219 inches and 0.229 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.590 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.045 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

17.000 at 200 pct single location and 200.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0