NSN 5925-00-103-1738

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-103-1738

Body Style: Rectangular dimensional envelope Overall Length: 10.750 inches **Overall Height:** 4.062 inches **Overall Width:** 8.250 inches **Unthreaded Mounting Hole Diameter:** 0.312 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 300.0 amperes ac all locations and 300.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac and 250.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two Adjustable Trip Setting Current Range Per Pole In Amps: +1500.0/+3000.0 ac and +1500.0 to 3000.0 dc all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

90.000 at 200 pct and 550.000 at 200 pct all locations

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

NSN 5925-00-103-1738

Circuit Breaker Tripper - Page 2 of 2



	Freq	uency	In	Hertz
--	------	-------	----	-------

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0