# NSN 5925-00-103-5152

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-103-5152

#### Body Style:

Rectangular dimensional envelope

**Overall Length:** 

10.750 inches

### **Overall Height:**

4.062 inches

#### **Overall Width:**

8.250 inches

#### **Unthreaded Mounting Hole Diameter:**

0.312 inches

**Fragility Factor:** 

Moderately rugged

#### **Pole Quantity:**

3

#### Mounting Facility Type And Quantity:

4 unthreaded hole

#### Storage Type:

General purpose warehouse

#### Maximum Continuous Load Current Rating Per Pole:

350.0 amperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

#### Circuit Protection Type:

Overcurrent all locations

#### Trip Release Method:

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### Manual Actuator Type And Quantity:

1 toggle

# Actuator Function:

Trip-reset

# Actuator Position Designation:

At pole two

# Trip Delay Time In Seconds Per Rated Continuous Current:

 $90.000\,$  at 200 pct all locations and  $550.000\,$  at 200 pct all locations

# Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

### Frequency In Hertz:

60.0 all locations

# NSN 5925-00-103-5152

Circuit Breaker Tripper - Page 2 of 2



# Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0