## NSN 5925-00-103-5157



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-103-5157 **Body Style:** Multipole-single actuator type **Mounting Slot Width:** 0.562 inches **Body Length:** 3.016 inches **Body Width:** 2.000 inches **Body Height:** 3.375 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Boss Height:** 0.187 inches **Pole Quantity:** 2 **Mounting Facility Type And Quantity:** 2 slot **Storage Type:** General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

**Manual Actuator Type And Quantity:** 1 toggle

## **NSN 5925-00-103-5157** Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
40.000 at 150 pct all locations and 500.000 at 150 pct all locations
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
50.0 all locations
Terminal Type And Quantity:
2 clip and 2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0