NSN 5925-00-104-3516

Circuit Breaker - Page 1 of 2



Body Style:
Multipole-single actuator type
Bushing Length:
0.380 inches
Body Length:
1.562 inches
Body Width:
1.281 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
Between 0.844 inches and 0.906 inches
Center To Center Distance Between Terminals Parallel To Width:
Between 0.594 inches and 0.656 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.780 inches
Pole Quantity:
2
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
Maximum Continuous Load Current Rating Per Pole: 7.0 amperes ac all locations and 7.0 amperes dc all locations
7.0 amperes ac all locations and 7.0 amperes dc all locations
7.0 amperes ac all locations and 7.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts:
7.0 amperes ac all locations and 7.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 50.0 dc all locations
7.0 amperes ac all locations and 7.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 50.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
7.0 amperes ac all locations and 7.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 50.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations and 1000.0 dc all locations
7.0 amperes ac all locations and 7.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 50.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations and 1000.0 dc all locations Circuit Protection Type:
7.0 amperes ac all locations and 7.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 50.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations and 1000.0 dc all locations Circuit Protection Type: Overcurrent all locations
7.0 amperes ac all locations and 7.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 50.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations and 1000.0 dc all locations Circuit Protection Type: Overcurrent all locations Trip Release Method:
7.0 amperes ac all locations and 7.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 50.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations and 1000.0 dc all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations

115.0 all locations

NSN 5925-00-104-3516 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.070 at 200 pct all locations and 0.700 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Hermetically sealed and shockproof and vibrationproof
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
3.600 ounces
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0