

View Online at <https://aerobasegroup.com/nsn/5925-00-104-8538>

Body Style:

Rectangular dimensional envelope

Overall Length:

10.750 inches

Overall Height:

4.062 inches

Overall Width:

8.250 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

300.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Trip Delay Time In Seconds Per Rated Continuous Current:

90.000 at 200 pct all locations and 550.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0