## NSN 5925-00-104-8539



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-104-8539 **Body Style:** Multipole-single actuator type **Body Length:** 3.016 inches **Body Width:** 3.000 inches **Body Height:** 2.375 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.150 inches **Pole Quantity: Mounting Facility Type And Quantity:** 3 terminal **Storage Type:** General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 35.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

1 toggle

**Manual Actuator Type And Quantity:** 

## **NSN 5925-00-104-8539** Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
240.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
3 compression and 3 clip
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0