

View Online at <https://aerobasegroup.com/nsn/5925-00-105-1981>

**Body Style:**

Multipole-single actuator type

**Body Length:**

Between 5.990 inches and 6.010 inches

**Body Width:**

Between 4.115 inches and 4.135 inches

**Body Height:**

Between 3.180 inches and 3.200 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 5.240 inches and 5.260 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 1.370 inches and 1.390 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 4.710 inches and 4.730 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.370 inches and 1.390 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.180 inches and 0.200 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

5 unthreaded hole and 6 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

20

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

7500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

140.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Thread Size:**

0.250 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

30.000 at 200 pct all locations and 100.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant and moisture resistant and vibration resistant and shock resistant and salt spray proof and sand resistant and dustproof

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0