

View Online at <https://aerobasegroup.com/nsn/5925-00-105-1981>

Body Style:

Multipole-single actuator type

Body Length:

Between 5.990 inches and 6.010 inches

Body Width:

Between 4.115 inches and 4.135 inches

Body Height:

Between 3.180 inches and 3.200 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 5.240 inches and 5.260 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 1.370 inches and 1.390 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.710 inches and 4.730 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.370 inches and 1.390 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.180 inches and 0.200 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

5 unthreaded hole and 6 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

20

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Thread Size:

0.250 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 200 pct all locations and 100.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant and vibration resistant and shock resistant and salt spray proof and sand resistant and dustproof

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0