

View Online at <https://aerobasegroup.com/nsn/5925-00-106-2675>

Body Style:

Multipole-single actuator type

Overall Height:

5.790 inches

Body Length:

10.125 inches

Body Width:

5.500 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

8.876 inches

Center To Center Distance Between Terminals Parallel To Width:

1.719 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.438 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.719 inches

Boss Height:

0.500 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

225.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 ac all locations

Circuit Protection Type:

Undervoltage all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

120.0 all locations

Ultimate Trip Time Per Pole In Seconds:

1.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

3 control

Internal Trip Release Configuration:

Relay trip all locations

Switch Location And Position Designation:

Internal at pole three

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Switch Terminal Type:

Wire lead

Switch Current Rating And Type In Amps:

10.0 ac

Switch Voltage Rating And Type In Volts:

120.0 ac

Special Features:

Silver main and arcing contacts

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0