## NSN 5925-00-106-5263

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-106-5263

Body Style:
Multipole-multiple actuator type
Body Length:
2.500 inches
Body Width:
1.500 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.938 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.140 inches
Mounting Surface To Terminal End Distance:
Between 2.549 inches and 2.673 inches
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
4 threaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
7.8 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac all locations
Circuit Protection Type:

Overcurrent all locations

## **NSN 5925-00-106-5263** Circuit Breaker - Page 2 of 2



Trip Release Method:
Magnetic-hydraulic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.500 at 200 pct and 10.000 at 200 pct all locations
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
0.547 pounds
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0