NSN 5925-00-109-2198

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-109-2198 **Body Style:** Single pole type **Overall Length:** 2.000 inches **Body Width:** 1.250 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 0.906 inches **Unthreaded Mounting Hole Diameter:** 0.203 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.574 inches **Mounting Surface To Terminal End Distance:** 1.266 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 unthreaded hole **Storage Type:** General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 575.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 130.0 single location **Reset Method:** Manual

Trip free

Main Contact Tripping Mechanism Type:

NSN 5925-00-109-2198 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 push button
Actuator Function:
Reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Trip Delay Time In Seconds Per Rated Continuous Current:
7.000 at 200 pct single location and 70.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Dustproof and shockproof
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A030a0