

View Online at <https://aerobasegroup.com/nsn/5925-00-109-9161>

**Body Style:**

Multipole-single actuator type

**Body Length:**

17.000 inches

**Body Width:**

Between 8.000 inches and 8.500 inches

**Unthreaded Mounting Hole Diameter:**

1.031 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

14.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.750 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

800.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Manual Actuator Type And Quantity:**

1 toggle

**Trip Delay Time In Seconds Per Rated Continuous Current:**

280.000 at 200 pct all locations and 950.000 at 200 pct all locations

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Special Features:**

Main contacts protected by arcing contacts, arc barriers and magnetic blowouts; main contacts self-aligning, self-cleaning and removable

**Frequency In Hertz:**

60.0 all locations

**Special Test Features:**

Dielectric strength must pass equivalent of 1960v between live parts and ground and between poles for 1 second in both open and closed positions; must interrupt 350 percent at 60 hz of its rated current at 208v for 30 operations at 10 second intervals without undue burning of contacts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0