NSN 5925-00-110-7281



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-110-7281 **Body Style:** Rectangular dimensional envelope **Overall Length:** 15.500 inches **Overall Height:** 4.062 inches **Overall Width:** 9.000 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.375 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 6 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 600.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 30000.0 ac all locations **Circuit Protection Type:** Undervoltage single location **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations

Reset Method: Manual

Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-00-110-7281 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and corrosion resistant and moisture resistant
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
33.000 pounds
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0