NSN 5925-00-116-4888



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-116-4888 **Body Style:** Multipole-single actuator type **Mounting Slot Width:** 0.094 inches **Body Length:** 2.875 inches **Body Width:** 3.000 inches **Body Height:** 2.375 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Boss Height:** 0.187 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 slot **Storage Type:** General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:**

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

NSN 5925-00-116-4888 Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
3 clip and 3 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0