NSN 5925-00-122-0053

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-122-0053

#### **Body Style:**

Multipole-single actuator type

#### **Body Length:**

3.000 inches

## Body Width:

2.000 inches

#### **Body Height:**

2.375 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Width:

1.000 inches

#### **Boss Height:**

0.187 inches

#### **Pole Quantity:**

2

#### Mounting Facility Type And Quantity:

4 terminal

## Storage Type:

General purpose warehouse

## Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### Trip Release Method:

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

#### Manual Actuator Type And Quantity:

1 toggle

#### **Actuator Function:**

Trip-reset

# NSN 5925-00-122-0053

Circuit Breaker - Page 2 of 2



**Actuator Position Designation:** 

At each pole

#### Trip Delay Time In Seconds Per Rated Continuous Current:

14.000 at 200 pct all locations and 115.000 at 200 pct all locations

#### Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

## Trip Release Ambient Tempurature Rating:

40.0 degrees celsius all locations

### **Frequency In Hertz:**

60.0 all locations

#### Terminal Type And Quantity:

2 screw and 2 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A030a0