

View Online at <https://aerobasegroup.com/nsn/5925-00-132-2203>

Body Style:

Single pole type

Bushing Length:

0.319 inches

Body Length:

1.765 inches

Body Width:

0.635 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.110 inches and 1.140 inches

Switch Contact Arrangement:

Single pole, double throw

Mounting Surface To Terminal End Distance:

1.753 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

50.0 milliamperes ac single location and 50.0 milliamperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location and 2500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

2 alarm

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.469 inches

Switch Location And Position Designation:

Internal at pole one

Inclosure Protection Type For Which Designed:

Vibration resistant and shock resistant and corrosion resistant and moisture resistant and fungus resistant and sand resistant and dusttight

Switch Terminal Type:

Turret

Switch Current Rating And Type In Amps:

4.0 ac and 4.0 dc

Switch Voltage Rating And Type In Volts:

130.0 ac and 28.0 dc

Frequency In Hertz:

60.0 single location

Unpackaged Unit Weight:

2.000 ounces

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0