## NSN 5925-00-136-6935

Circuit Breaker - Page 1 of 3

Multipole-single actuator type

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5925-00-136-6935

Bushing Length:
0.375 inches
Body Length:
1.495 inches
Body Width:
1.872 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.875 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
Between 0.620 inches and 0.630 inches
Nonturn Device Diameter:
0.138 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.678 inches
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
15.0 amperes ac second location
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac third location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
300.0 ac second location

## NSN 5925-00-136-6935

Circuit Breaker - Page 2 of 3



Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic-hydraulic all locations
Trip Release Characteristic:
Time delay third location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
1.000 at 200 pct third location and 4.000 at 200 pct third location
Inclosure Protection Type For Which Designed:
Fungus resistant and hermetically sealed and moisture resistant
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
4.500 ounces
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 wire hook
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 5925-00-136-6935

Circuit Breaker - Page 3 of 3



Fiig:

A030a0