

View Online at <https://aerobasegroup.com/nsn/5925-00-139-4829>

Body Style:

Multipole-single actuator type

Body Length:

5.260 inches

Body Width:

2.984 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

4.359 inches

Center To Center Distance Between Terminals Parallel To Width:

0.490 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

End Application:

Asr7

Boss Height:

0.219 inches

Mounting Surface To Terminal End Distance:

3.313 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

8.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.700 at 150 pct all locations and 1.200 at 150 pct all locations and 0.300 at 200 pct all locations and 0.900 at 200 pct all locations and 0.150 at 300 pct all locations and 0.300 at 300 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0